

PROJECT INFORMATION:

PAVEMENT REMOVAL AND REPLACEMENT PERMIT

Troject Name.	Project Name:				
Project Location/Address:					
Subdivision Name:			Block:		
Paving Type:	☐ Driveway ☐ Parking Lot/Drive Isle ☐ Replace Asphalt	☐ Dump ☐ New :	☐ Barrier Free Ramps ☐ Dumpster Pad ☐ New Asphalt (requires Council approval)		
PROPERTY OWNER INFORMATIO	N: CONTR	RACTOR INFOI	RMATION:		
Company Name:	Compan	y Name:			
Contact Name:	Contact	Name:			
Contact Name.					
	Address:	•			
Address:Phone No.:					

Mix Design (required)	Other:	
☐ Site Plan / Area of Construction (required)		
Typical Sections		
☐ Traffic Control Plan (required if work to be performed in		

Replacement Steel Reinforced Concrete Pavement Requirements

Street/Pavement Type	Minimum Thickness (inches)	Strength 28-day (psi)	Minimum Cement (sacks/cy)		Min. Steel Reinforcement	
			Machine Placed	Hand Placed	Bar#	Spacing (O.C.E.W)
Collector	8"	3,600	6.0	6.5	#4 bars	18"
Residential	7" *	3,600	6.0	6.5	#4 bars	18"
Fire Lane	7" *	3,600	6.0	6.5	#3 bars	24"
Driveways**	7" *	3,600	6.0	6.5	#3 bars	24"
Barrier Free Ramps	6"	3,600	N/A	6.5	#3 bars	24"
Sidewalks	4"	3,000	N/A	5.5	#3 bars	24"
Parking Lot/Drive Isles	6" *	3,000	5.0	5.5	#3 bars	24"
Dumpster Pads	7"	3,600	6.0	6.5	#3 bars	24"

^{*}Replacement pavement shown as 1" thicker than minimum pavement thicknesses.

City or TxDOT ROW. Signed by a licensed professional engineer)

^{**}Non-residential driveway



The City of Rockwall, herein called the City, authorizes _______, herein called the Permitee, to remove and replace the paving listed in this permit. 1. The Permitee agrees to comply with the City's current Standards for Design and Construction. 2. All construction materials shall be subject to inspection by the City's Engineering Construction Inspector listed below. 3. The Permitee shall contact the City's Inspector at least twenty-four (24) hours prior to beginning work on this authorized permit. 4. The Permitee shall contact the City's Inspector at least twenty-four (24) hours for inspections. 5. The Permitee shall hold harmless the City and dully appointed agents and employees against any action for personal injury or property damage sustained by reason of the exercise of this permit. 6. This permit will be null and void if not constructed within six (6) months from the issuance date of this permit. 7. Approved permit must be kept onsite at all times while under construction or inspection. 8. All fill requires 95% compaction with densities. Densities may be required based on existing subgrade conditions if deficiencies are noticed after paving has been removed. 9. Concrete test cylinders will be required on all pours 10 yards or more. Pours less than 10 yards may require test cylinders as required by the Engineering Inspector. Permitee shall contact the Engineering Inspector for this determination prior to start of construction. 10. Mix design must be verified prior to concrete placement. 11. All lab results are to be emailed to the City Inspector. Permitee (signature): Date: _____ Permitee (printed): For City Use: City Engineering Inspector: Inspector Phone Number: ___ Engineering Department: 972-771-7746 City Engineering Authorized Representative Date of Issuance Batch Design Verification Subgrade Reinforcement Pavement Thickness ☐ Reinforcement ☐ Densities (if required) ☐ Cylinder Compression Testing Compression Testing Passed Other _____ Comments: Inspector Signature Date of Completion